

Operator
Telephone
Fax
e-Mail

TONS DG-9925RL(ZHT-C35-36D) / UGR-Table

Luminaire: TONS DG-9925RL(ZHT-C35-36D)

Lamps: 1 x LUMINUS CXM-4-30-90-36-TE60-F7-2 200mA

Glare Evaluation According to UGR											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	-0.1	0.6	0.2	0.8	1.0	-0.1	0.6	0.2	0.8	1.0
	3H	-0.2	0.4	0.1	0.6	0.8	-0.2	0.4	0.1	0.6	0.8
	4H	-0.3	0.3	0.0	0.5	0.8	-0.3	0.3	0.0	0.5	0.8
	6H	-0.3	0.2	-0.0	0.4	0.7	-0.3	0.2	-0.0	0.4	0.7
	8H	-0.4	0.1	-0.0	0.4	0.7	-0.4	0.1	-0.0	0.4	0.7
	12H	-0.4	0.0	-0.1	0.3	0.7	-0.4	0.0	-0.1	0.3	0.7
4H	2H	-0.3	0.3	0.0	0.5	0.8	-0.3	0.3	0.0	0.5	0.8
	3H	-0.4	0.0	-0.1	0.3	0.7	-0.4	0.0	-0.1	0.3	0.7
	4H	-0.5	-0.1	-0.1	0.2	0.6	-0.5	-0.1	-0.1	0.2	0.6
	6H	-0.6	-0.2	-0.2	0.1	0.5	-0.6	-0.2	-0.2	0.1	0.5
	8H	-0.6	-0.3	-0.2	0.1	0.5	-0.6	-0.3	-0.2	0.1	0.5
	12H	-0.6	-0.4	-0.2	0.0	0.4	-0.6	-0.4	-0.2	0.0	0.4
8H	4H	-0.6	-0.3	-0.2	0.1	0.5	-0.6	-0.3	-0.2	0.1	0.5
	6H	-0.7	-0.5	-0.2	-0.1	0.4	-0.7	-0.5	-0.2	-0.1	0.4
	8H	-0.7	-0.6	-0.3	-0.1	0.3	-0.7	-0.6	-0.3	-0.1	0.3
	12H	-0.8	-0.6	-0.3	-0.2	0.3	-0.8	-0.6	-0.3	-0.2	0.3
12H	4H	-0.6	-0.4	-0.2	0.0	0.4	-0.6	-0.4	-0.2	0.0	0.4
	6H	-0.7	-0.6	-0.3	-0.1	0.3	-0.7	-0.6	-0.3	-0.1	0.3
	8H	-0.8	-0.6	-0.3	-0.2	0.3	-0.8	-0.6	-0.3	-0.2	0.3
Variation of the observer position for the luminaire distances S											
S = 1.0H		+5.5 / -20.4					+5.5 / -20.4				
S = 1.5H		+8.3 / -29.6					+8.3 / -29.6				
S = 2.0H		+10.3 / -30.5					+10.3 / -30.5				
Standard table		BK00					BK00				
Correction Summand		-19.6					-19.6				
Corrected Glare Indices referring to 730lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.