PENDANT LUMINAIRES

PA-114A(O5)





Features & Application

- Simple and elegant, easy to install
- Accurate optical design ensures visual comfort

For residential and commercial applications; such as galleries, exhibition, cafeteria, bars etc.

Selectable color temperature：2700K、3000K、4000K

Photometric data



H(m)	D(m)	E(lx)
1.0	0.2	3400
2.0	0.4	850
3.0	0.6	378



H(m)	D(m)	E(lx)
1.0	0.4	1920
2.0	0.7	480
3.0	1.1	213



H(m)	D(m)	E(lx)
1.0	0.5	1060
2.0	1.1	265
3.0	1.6	118



H(m)	D(m)	E(lx)
1.0	0.7	830
2.0	1.5	208
3.0	2.2	92

Product specifications

Light Source	OSRAM LED (COB)	Material	Aluminum
LED Luminous flux	420 lm@3000K	Net Weight	/
Color rendering	RA>90		
Watts	6W(150mA)		
AC Input	220-240V · 50~60HZ		
Ballast/Transformer/Driver	Eaglerise： EBP006C015OS1(Built-in)		
Reflector Angle	12、20、30、40		
Standards of Safety	● EN 60598-1:2015 ● EN 60598-2-1:1989 ● EN 60598-2-6:1994+A1:1997		
Cord / Length / Connector	Terminals		
Color	WU、BK、SV		
Installation	Surface-mounted		
Storage Temperature Range	Temperature： -20℃ to +50℃/ Humidity： 85%		

Accessories

recessed ring (AC-2700A)

Version：1.0
2018.09.18